



RIGMASTER STANDS ALONE

The Ultimate Stand-Alone Truck-Mounted APU

MTS-T46K : Generator Model

Features

- Fully Self Contained, Stand-Alone Design
- 2 CYL, Tier 4 Final, EPA approved Engine (Kohler)
- Multiple Auto Start Features
- AC Generator: 6,000 Watts @ 120 VAC
- Alternator: 60 Amps For Battery Charging
- Air-Conditioning: 24,000 BTU; 600 CFM
- Heating: 13,500 BTU
- Fuel Consumption: 0.25 gal/hr (avg.)
- Large Oil Capacity: 1.24 gal (4.7 L)
- Compact HVAC Box:
12½" D x 15½" W x 8½" H



Benefits

- Easy Access to all Components
- Fast, Simple Installation
- Smaller, Lighter, & Quieter
- Dimensions:
25" D x 25" W x 28½" H
- Fits on Short Wheel Base Trucks
- Reduced maintenance due to Serpentine belt system
- Heat or No Heat Options
- Various mounting applications for the APU (frame rail or catwalk)



Dual-Blower
HVAC Box



Scan the QR code
to visit RigMaster





RigMaster... Discover the Difference!

Call us: 1-800-249-6222 ➤ www.rigmasterpower.com



RigMaster Technical Specifications

ATTRIBUTES	 MTS-T46K MTS-T46K-H		 LG200-K LG200-K-H	
	Heating (if applicable)	13,500 BTU – Built-in Automotive Style or Separate 7,000 BTU – Webasto Heater		
Air Conditioning	24,000 BTU			
Air Flow	600 CFM			
Alternator	60 Amps @ 12 Volts DC		Smart Alternator: 170 Amps @ 12 Volts DC	
Generator	6000 Watts @ 120 VAC; 2 x 20 Amps		N/A	
Inverter	N/A		Required (not included)	
Average Fuel Consumption	0.25 gal / hr			
Stand-Alone Unit	Yes			
Condenser/Radiator	Yes (built into main unit)			
Engine (Kohler)	Diesel, 2 Cylinder, Tier 4 Final, 10.5 HP @ 2400 RPM, 42 cu in (686 cc)			
Automatic Start Battery Protection	Yes			
Electric Fan	Yes			
Weight	410 lbs		335 lbs	
Additional Mounting Options	Catwalk Sub-frame: 50 lbs			
Main Unit Dimensions (Inches)	Width	25 "	Width	21 "
	Height	28 ½ "	Height	28 "
	Depth	25 "	Depth	25 "
HVAC Box Dimensions (Inches)	Width	15 ½ "	Width	15 ½ "
	Height	8 ½ "	Height	8 ½ "
	Depth	12 ½ "	Depth	12 ½ "



RIGMASTER STANDS ALONE

The Ultimate Stand-Alone Truck-Mounted APU

LG200-K : Inverter Model

Features

- Fully Self Contained, Stand-Alone Design
- 2 CYL, Tier 4 FINAL, EPA approved Engine (Kohler)
- Multiple Auto Start Features
- Alternator: 170 Amps For Battery Charging
- Air-Conditioning: 24,000 BTU; 600 CFM
- Heating: 13,500 BTU
- Fuel Consumption: 0.25 gal/hr (avg.)
- Large Oil Capacity: 1.24 gal (4.7 L)
- Compact HVAC Box:
12½" D x 15½" W x 8½" H



Benefits

- 360° Access to all Components
- Aluminum diamond plate cover
- Easy & Fast installation
- Ultra Quiet
- Extremely Lightweight
- Remarkably Compact
- Dimensions:
25" D x 21" W x 28" H
- Serpentine stretched-fit belt reduces maintenance
- Heat or No Heat Options
- Various mounting applications for the APU (frame rail or catwalk)

Dual-Blower HVAC Box



Scan the QR code to visit RigMaster





RigMaster... Discover the Difference!

Call us: 1-800-249-6222 • www.rigmasterpower.com



RigMaster Technical Specifications

ATTRIBUTES	 MTS-T46K MTS-T46K-H		 LG200-K LG200-K-H	
	Heating (if applicable)	13,500 BTU – Built-in Automotive Style or Separate 7,000 BTU – Webasto Heater		
Air Conditioning	24,000 BTU			
Air Flow	600 CFM			
Alternator	60 Amps @ 12 Volts DC		Smart Alternator: 170 Amps @ 12 Volts DC	
Generator	6000 Watts @ 120 VAC; 2 x 20 Amps		N/A	
Inverter	N/A		Required (not included)	
Average Fuel Consumption	0.25 gal / hr			
Stand-Alone Unit	Yes			
Condenser/Radiator	Yes (built into main unit)			
Engine (Kohler)	Diesel, 2 Cylinder, Tier 4 Final, 10.5 HP @ 2400 RPM, 42 cu in (686 cc)			
Automatic Start Battery Protection	Yes			
Electric Fan	Yes			
Weight	410 lbs		335 lbs	
Additional Mounting Options	Catwalk Sub-frame: 50 lbs			
Main Unit Dimensions (Inches)	Width	25 "	Width	21 "
	Height	28 ½ "	Height	28 "
	Depth	25 "	Depth	25 "
HVAC Box Dimensions (Inches)	Width	15 ½ "	Width	15 ½ "
	Height	8 ½ "	Height	8 ½ "
	Depth	12 ½ "	Depth	12 ½ "